



Committing to the future

Pocket-Sized Professional Measurement Technology

Measuring instruments for heating, air conditioning and ventilation

NEW!





Testo, the leading manufacturer of portable measurement technology, provides pocket-sized measuring instruments for fast and tough everyday use:

- Air temperature and infrared surface temperature
- Air humidity and temperature
- Material moisture, air humidity and temperature
- Differential pressure
- Absolute pressure
- rpm
- Light intensity
- Air flow velocity, temperature, humidity

Sensors which fulfil the highest demands, such as Testo's own patented humidity sensor, guarantee reliable and stable measurement results.

All instruments are very handy, small and easy to use. The backlit display and the Auto-Off function complete the instrument.


Always included:

Protective cap, wrist strap and belt holder – indispensable additions for practical use.

Great technology can be this small!

testo 810

Air temperature and infrared surface temperature in one instrument



- IR measurement with 1-point laser measurement spot marking and 6:1 optics
- Air temperature measurement
- Display of differential temperature e.g. between window and air
- Hold function and max./min. values

Surface temperature

Measuring range: -30 to 300 °C
 Resolution: 0.1 °C
 Accuracy: ±2.0 °C (-30 to +100 °C)
 ± 2% of m.v. (remaining range)

Optics: 6:1

Air temperature

Measuring range: -10 to 50 °C
 Resolution: 0.1 °C
 Accuracy: ± 0.5 °C
 Units: °C/°F
 Oper. temp.: -10 to 50 °C
 Battery type: Alkaline (2 x AAA)
 Battery life: 50 h. (average, without display illumination)


Dimensions (incl. protective cap): 119 x 46 x 25 mm

Included in delivery:
 Calibration protocol · Wrist strap
 Belt holder · Protective cap · Batteries

Order no. 0560 0810

testo 610

Air humidity and temperature



- Long-term drift-free Testo humidity sensor
- 2.5 %RH accuracy with calibration protocol
- Incl. dewpoint calculation and wet bulb
- Hold function and max./min. values

Temperature

Measuring range: -10 to 50 °C
 Resolution: 0.1 °C
 Accuracy: ± 0.5 °C
 Units: °C/°F

Humidity

Measuring range: 0 to 100 %RH
 Resolution: 0.1 %RH
 Accuracy: ± 2.5 %RH (5 to 95 %RH)
 Units: %RH, wet bulb, dewpoint

Oper. temp.: 10 to 50 °C
 Battery type: Alkaline (2 x AAA)
 Battery life: 200 h. (average, without display illumination)


Dimensions (incl. protective cap): 119 x 46 x 25 mm

Included in delivery:
 Calibration protocol · Wrist strap
 Belt holder · Protective cap · Batteries

Order no. 0560 0610

testo 606-1/2

Material moisture, air humidity and temperature



- Precise measurement of wood moisture thanks to stored characteristics curves for e.g. beech, spruce, larch, oak, pine, maple
- Air temperature and humidity for monitoring drying processes
- Characteristics curves for cement screed, concrete, plaster, anhydrite screed, cement mortar, lime mortar, brick
- Hold function
- Auto-test function

Material moisture

Measuring range: 0 to 90%
 Resolution: 0.1
 Accuracy: ± 1% (conductivity)

Air humidity (606-2 only)

Measuring range: 0 to 100%RH
 Resolution: 0.1%RH
 Accuracy: ±2.5%RH (5 to 95%RH)
 Units: %RH, wet bulb, dewpoint

Air temperature (606-2 only)

Measuring range: -10 to 50°C
 Resolution: 0.1°C
 Accuracy: ± 0.5 °C
 Units: °C/°F
 Oper. temp.: -10 to 50 °C
 Battery type: Alkaline (2 x AAA)
 Battery life: 606-1: 200 h.
 606-2: 130 h. (average, without display illumination)


Dimensions (incl. protective cap): 119 x 46 x 25 mm

Included in delivery:
 Calibration protocol · Wrist strap
 Belt holder · Protective cap · Batteries

606-1: Order no. 0560 6060
 606-2: Order no. 0560 6062

testo 410-1/-2

Air flow velocity, temperature and humidity



- Integrated measurement with 40 mm vane
- Timed mean value calculation
- Hold function and min./max. values
- Windchill calculation for outdoor areas

Flow velocity

Measuring range: 0.4 to 20 m/s
 Resolution: 0.1 m/s
 Accuracy: ± (0.2 m/s + 2% of m.v.)
 Units: m/s, km/h, fpm, mph, knots, perceived temperature °C/°F (windchill), Beaufort

Temperature

Measuring range: -10 to 50 °C
 Resolution: 0.1 °C
 Accuracy: ± 0.5 °C
 Units: °C/°F

Humidity (testo 410-2 only)

Measuring range: 0 to 100 %RH
 Resolution: 0.1 %RH
 Accuracy: ± 2.5 %RH (5 to 95 %RH)
 Units: %RH, wet bulb, dewpoint

Oper. temp.: -10 to 50 °C
 Battery type: Alkaline (2 x AAA)
 Battery life: testo 410-1: 100 h.
 testo 410-2: 60 h. (average, without display illumination)

Dimensions (incl. protective cap): 133 x 46 x 25 mm

Included in delivery:
 Calibration protocol · Wrist strap
 Belt holder · Protective cap · Batteries

410-1: Order no. 0560 4101
 410-2: Order no. 0560 4102



· 50 YEARS OF TESTO
 · More innovative than ever
 · 50 innovations in the anniversary year



INNOVATION 2007

testo 510

Differential pressure 0 to 100 hPa



- Possibility of display in Pascal over entire measuring range
- Temperature compensation
- Magnets on the rear allow free-hand work
- Flow velocity measurement with Pitot tube
- Air density compensation

Pressure

Measuring range: 0 to 100 hPa
 Resolution: 0.0 1hPa
 Accuracy: ± 0.03 hPa (0 to 0.30 hPa) ±0.05 hPa (0.31 to 1.00 hPa) ± (0.1 hPa +1.5% of m.v.) (1.01 hPa to 100 hPa)
 Units: hPa, mbar, Pa, mmH₂O, mmHg, inH₂O, inHg, psi, m/s, fpm
 Oper. temp.: 0 to 50 °C
 Battery type: Alkaline (2 x AAA)
 Battery life: 500 h. (average, without display illumination)
 Dimensions (incl. protective cap): 119 x 46 x 25 mm

Included in delivery:

Calibration protocol · Wrist strap
 Belt holder · Protective cap · Batteries

Order no. 0560 0510

testo 511

Absolute pressure, barometric pressure, altitude



- Absolute pressure ±3 hPa
- Calculation of barometric air pressure
- Barometric altitude measurement

Pressure

Measuring range: 300 to 1,200 hPa
 Resolution: 0.1 hPa
 Accuracy: ± 3.0 hPa
 Units: hPa, mbar, Pa, mmH₂O, mmHg, inH₂O, inHg, psi, m, ft
 Oper. temp.: 0 to 50 °C
 Battery type: Alkaline (2 x AAA)
 Battery life: 500 h. (average, without display illumination)
 Dimensions (incl. protective cap): 119 x 46 x 25 mm

Included in delivery:

Calibration protocol · Wrist strap
 Belt holder · Protective cap · Batteries

Order no. 0560 0511

testo 460

rpm, optical



- Optical rpm measurement with LED measurement spot marking
- Max./min. values

rpm

Measuring range: 100 to 29,999 rpm
 Resolution: 0.1 rpm (100 to 999.9 rpm) 1 rpm (1,000 to 29,999 rpm)
 Accuracy: ± (0.02 % of m.v.) + 1 digit
 Units: rpm, rps
 Oper. temp.: 0 to 50 °C
 Battery type: Alkaline (2 x AAA)
 Battery life: 20 Std. (average, without display illumination)
 Dimensions (incl. protective cap): 119 x 46 x 25 mm

Included in delivery:

Calibration protocol · Wrist strap
 Belt holder · Protective cap · Batteries

Order no. 0560 0460

testo 540

Light intensity



- Sensor is adjusted to the spectral sensitivity of the eye
- Hold function for easy measurement value readout
- Max./min. values

Light intensity

Measuring range: 0 to 99,999 Lux
 1 Lux (0 to 19,999 Lux)
 10 Lux (20,000 to 99,999 Lux)
 Accuracy: ± 3% (compared to reference)
 Units: Lux, Footcandle
 Oper. temp.: 0 to 50 °C
 Battery type: Alkaline (2 x AAA)
 Battery life: 20 Std. (average, without display illumination)
 Dimensions (incl. protective cap): 133 x 46 x 25 mm

Included in delivery:

Calibration protocol · Wrist strap
 Belt holder · Protective cap · Batteries

Order no. 0560 0540



Pocket-Sized Professional Measurement Technology



- 50 YEARS OF TESTO
- More innovative than ever
- 50 innovations in the anniversary year



INNOVATION 2007